

序号No.	配件名称 Spare Parts	材料 Material	6	填料 Packing	12	铜螺母 Nut	压铸黄铜 Brass
1	底板 Bottom plate	Q235(Cr. D)	7	压板 Packing Gland	13	平面轴承 Bearing	GGCr15
2	阀体 Body	GGG40	8	夹头 Chuck	14	手轮 Handwheel	GGG40
3	闸板 Disc	SS304	9	支架板 Yoke	15	井帽 Nut	Q235(Cr. D)
4	阀座 Seat	NR	10	阀杆 Stem	16	堵头 Plug	Q235(Cr. D)
5	导向垫 Guide Pad	PTFE	11	支架头 Yoke Head		标准件 Bolts/Nuts	A2-70

备注 (Note): 1、设计按 (Design): JB/T8691-2013
2、法兰按 (Flange): GB/T9113.1-2010
3、结构长度按 (Face to face):
GB/T15188.2-94 chart6-7
4、试验和验收 (Testing): GB/T13927-2022

刀闸阀主要外形及连接尺寸 Outline and Dimension

型号 Model: QWZ73NM-10G

通径	尺寸 size										
	DN (mm)	L	L1	D	D1	D2	D0	N-Th	T	●	⊕
50	53	55	165	125	99	180	4-M16	12	4	0	0.18
65	53	55	185	145	118	200	4-M16	12	4	0	0.18
80	55	57	200	160	132	220	8-M16	12	4	0	0.18
90	55	57	210	170	142	220	8-M16	12	4	0	0.18
100	55	57	220	180	156	240	8-M16	12	4	0	0.18
125	62	64	250	210	184	260	8-M16	14	4	0	0.18
150	62	64	285	240	211	280	8-M20	14	4	0	0.23
175	62	64	305	265	237	280	12-M20	14	4	0	0.23
200	75	77	340	295	266	300	8-M20	18	4	0	0.23
225	75	77	350	310	282	300	12-M20	18	4	0	0.23
250	75	77	395	350	319	320	12-M20	18	4	0	0.23
300	82	84	445	400	370	350	12-M20	20	8	4	0.23
350	82	84	505	460	429	400	16-M20	20	12	4	0.23
400	95	99	565	515	480	450	16-M24	24	12	4	0.27
450	95	99	615	565	530	500	20-M24	24	16	4	0.27
500	125	129	670	620	582	0	20-M24	27	16	4	0.27
550	125	129	725	680	638	0	20-M27	27	16	4	0.30
600	125	129	780	725	682	0	20-M27	27	16	4	0.30
650	125	129	845	780	732	0	24-M27	27	20	4	0.30
700	138	143	895	840	794	0	24-M27	27	20	4	0.30
750	138	143	970	900	855	0	24-M30	30	20	4	0.33
800	138	143	1015	950	901	0	24-M30	30	20	4	0.33
850	138	143	1070	1000	955	0	28-M30	30	24	4	0.33
900	138	143	1115	1050	1001	0	28-M30	30	24	4	0.33
1000	159	163	1230	1160	1112	0	28-M33	33	24	4	0.36
1100	159	163	1340	1260	1220	0	28-M33	33	24	4	0.36
1200	166	172	1455	1380	1338	0	32-M36	36	28	4	0.39
1350	181	187	1630	1540	1480	0	36-M39	39	32	4	0.42
1400	181	187	1675	1590	1530	0	36-M39	39	32	4	0.42
1500	208	214	1795	1705	1640	0	40-M39	39	36	4	0.42
1600	208	214	1915	1820	1750	0	40-M45	45	36	4	0.48
1800	229	235	2115	2020	1950	0	44-M45	45	40	4	0.48
2000	260	266	2325	2230	2150	0	48-M45	45	44	4	0.48

